

Compiling PARI from the GIT repository

B. Allombert and K. Belabas

IMB
CNRS/Université de Bordeaux

27/02/2023



Introduction

This talk focuses on the current development version of the PARI library (2.16.*), available from our GIT repository, see

<https://pari.math.u-bordeaux.fr/anongit.html>

The text of this talk is available in the files `sources.*` in

[https://pari.math.u-bordeaux.fr/Events/
PARI2023/talks/](https://pari.math.u-bordeaux.fr/Events/PARI2023/talks/)

Windows users

Download a precompiled 64bit installer [Pari64-2-16-0.exe](#) or 32bit binary [Pari32-2-16-0.exe](#) from

<https://pari.math.u-bordeaux.fr/pub/pari/unstable>

Also available are precompiled 64bit binary [gp64-gmp-git*.exe](#) or 32bit binary [gp32-gmp-git*.exe](#). Or you can use the "Windows subsystem for Linux", see <https://pari.math.u-bordeaux.fr/PDF/PARIwithWindows.pdf>

Mac OS users

Download a precompiled DMG `PariGP-full-2.16.0.dmg`
or `PariGP-arm-full-2.16.0.dmg`

`https://pari.math.u-bordeaux.fr/pub/pari/unstable`

on some system, you need to go to the file menu and select open, so that you can bypass the security check.
Also are precompiled binary `gp-git*-osx`.

Linux

To install all the packages required to build pari from source:

Debian/Ubuntu

```
sudo apt-get build-dep pari
sudo apt-get install libreadline-dev libgmp-dev
```

Fedora

```
sudo dnf install readline-devel gmp-devel
```

If you want to use git, also do

Debian/Ubuntu

```
sudo apt-get install git bison automake autoconf
```

Fedora

```
sudo dnf install git bison automake autoconf
```

From source with GIT

Clone the PARI repository with GIT (~ 150MB).

```
git clone https://pari.math.u-bordeaux.fr/git/pari.git
cd pari
```

From source without GIT

Download `pari-2.16.0.alpha.tar.gz` from

`https://pari.math.u-bordeaux.fr/pub/pari/unstable`

and unpack it

```
tar xf pari-2.14*.tar.gz
cd pari-2.14*
```

PARI compilation

```
./Configure --prefix=GPDIR --mt=pthread  
make -j4 gp  
make doc  
make statest-all  
make install  
make install-bin-sta  
./Configure --prefix=GPDIR.dbg -g  
make -j4 gp.dbg  
make install -C Olinux-x86_64.dbg  
GPDIR/bin/gp
```


Optional PARI packages

To install optional PARI packages from

<https://pari.math.u-bordeaux.fr/packages.html>

```
wget https://pari.math.u-bordeaux.fr/\
pub/pari/packages/galdata.tgz
```

```
tar xf galdata.tgz
```

```
wget https://pari.math.u-bordeaux.fr/\
pub/pari/packages/elldata.tgz
```

```
tar xf elldata.tgz
```

```
wget https://pari.math.u-bordeaux.fr/\
pub/pari/packages/galpol.tgz
```

```
tar xf galpol.tgz
```

```
wget https://pari.math.u-bordeaux.fr/\
pub/pari/packages/seadata.tgz
```

```
tar xf seadata.tgz
```

Optional PARI packages

```
wget https://pari.math.u-bordeaux.fr/\
pub/pari/packages/nflistdata.tgz
tar xf nflistdata.tgz
make install-data
```

GP configuration

Create and customize `~/.gprc`. Add

```
histfile = "~/.gp_history"
colors = "lightbg" \\ or "darkbg"
lines = 40
parisizemax = 4G \\ or the maximum amount of memory
                \\ GP can use (important)
threadsizemax = 1G
read "~/.gprc.gp"
```

Create an empty file `~/.gprc.gp`

GP2C compilation

With GIT (and automake, autoconf):

```
git clone https://pari.math.u-bordeaux.fr/git/gp2c.git
cd gp2c
./autogen.sh
```

Without GIT: download GP2C from <https://pari.math.u-bordeaux.fr/download.html#gp2c>

```
tar xf gp2c-0.0.12.tar.gz
cd gp2c-0.0.12
```

GP2C compilation

```
./configure --prefix=$PWD/../GPDIR \  
    --with-paricfg=../GPDIR/lib/pari/pari.cfg \  
    --with-paricfg.dbg=../GPDIR.dbg/lib/pari/pari.cfg  
make check  
make install  
cd ..  
GPDIR/bin/gp2c -v
```

Updating GIT

To update GIT to the most recent revision:

```
git fetch
git rebase origin/master
./Configure -l
make install
```

Changelog

You can see the latest commits with

```
git log
```